



Reliance Supply Company

Cobble Coat H2O Clear Sealer for Concrete/Pavers/Stone

Cobble Coat H2O is the newest technology in waterborne protection for Texture Deck, concrete and brick pavers. Cobble Coat H2O may also be used over travertine, natural stone and most porous surfaces as it has excellent water resistance and marking resistance. Cobble Coat H2O is an excellent topcoat over our Colorcrete Sealer where added protection and wear are needed.

Characteristics and Technical Data

% Solids by Wt.(+/- 3%)	28%
Gardner Gloss @ 60	90
QUV (ASTM D G-53)	2000 hours no gloss loss
WT./GL.:	8.5lbs
Coverage:	200-300 SqFt./Gl. @ 2 mil DFT
Clean Up:	Water
VOC's	260G/L

Directions

Stir product. Surfaces must be clean and dry before sealing. Cobble Coat H2O's performance is directly related to how thoroughly the surface is prepared. All grease, oil and potential contaminants must be removed. Concrete should cure a minimum of 28 days before sealing. Read label instructions carefully. Smooth concrete must be etched. Cobble Clean and Cobble Prep may be used for specific cleaning situations. Two thin coats(2 dry mils) provide the best results. Do not apply when the temperature of the air or the surface to be coated is below 50F. Testing the product on your surface is always recommended to ensure desired results.

Dry Times

Dry to touch: 30 minutes
Light traffic and recoat: 3 to 4 hours
Full cure: 48 to 72 hours

Packaging & Unit Shipping Weight

1- gal cans- 4 gal. per case- 40 cases per pallet: 35 lbs per case
5- gal pails- 36 pails per pallet: 45 lbs per pail

Warning: Coated surfaces may become slippery. Reliance Supply's non-skid additive should be incorporated in this situation. However, it is the sole responsibility of the applicator to determine whether a non-skid additive should be incorporated and if it will work for their job..

Use with adequate ventilation.

All Reliance Supply Company products are manufactured with the finest raw materials. The shelf life is 12 months from date of purchase when maintained in protected storage of 50F to 90F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without guarantee, since the conditions of use are beyond our control.



Reliance Supply Company

1880 N.W. 18th Street ♦ Pompano Beach, FL 33069
Phone: 954.971.9111 ♦ Fax 954.971.6623
Reliance-Supply.com